

Radionuclide Safety Data Sheet

RADIONUCLIDE: Bi-206

FORMS: Soluble

PHYSICAL CHARACTERISTICS

Half-life: 6.243 days

DECAY EMISSIONS

Gammas / X-rays		Betas / Positrons (+) / Electrons		Alphas	
E (keV)	%	E (keV, max)	%	E (keV)	%
803.1	99.0	56.7	4.2		
895.12	15.67	95.97	21.6		
1098.26	13.51	168.12	3.71		
1718.7	31.9	255.5	5.70		

Only the four most likely emissions of each type are included. Emission must be > 10 keV and > 1% frequency.

NIH HAZARD CATEGORY

C – level (low hazard): n/a

B – level (moderate hazard): n/a

A – level (high hazard): Any Quantity of Bi-206 - DRS protocol required

EXTERNAL RADIATION HAZARDS

Gamma dose rate, point source @ 1 foot, 1 mCi:

Beta dose rate to skin, point source @ 1 foot, 1 mCi:

Contamination skin dose, uniform deposit of 1 $\mu\text{Ci}/\text{cm}^2$

INTERNAL RADIATION HAZARDS

Annual Limit on Intake:

Ingestion: 600 μCi

Inhalation: 900 μCi

The value(s) above indicate the activity taken into the body that would result in either 5 rem to the whole body (CEDE) or 50 rem to an organ or tissue (CDE).

SHIELDING

Gammas/X-rays:

33.7 mm Pb will decrease exposure by 90%.

Betas/electrons:

1 mm Lucite will stop all betas. Lead may be needed if Bremsstrahlung is detectable through plastic.

DOSIMETRY AND BIOASSAY REQS

Dosimetry may be required when working with Bi-206. Fill out Dosimetry Evaluation Form, and DRS will determine if it is required.

Whole body count may be required after spills, contamination, or other abnormal occurrences.

SPECIAL PRECAUTIONS:

1. Contamination monitoring for Bi-206 should be performed with a Sodium Iodide probe.
2. Bi-206 should be handled with remote tools when possible.
3. Ensure Bi-206 is properly shielded when in storage and use. Shield waste containers containing Bi-206 waste.
4. Always wear lab coat, gloves, and protective eyewear when handling Bi-206.
5. Source vials must be secured in a locked container when not in use.
6. Bi-206 waste must be segregated from long half-life radionuclides (> 120 days). Multi-hazard waste must be segregated from medium and long half-life radionuclides (> 30 days but $\leq$ 120 days and > 120 days respectively).
7. A DRS protocol is required to possess any activity of Bi-206.

References:

- Brookhaven National Laboratory, National Nuclear Data Center, Decay Radiation Search, Version 3/25/2022.
- National Institutes of Health Division of Radiation Safety, DRS-214 Form - Activity Control System - Cumulative Inventory Ceilings, Revised 10/4/2021.
- Nuclear Regulatory Commission, 10 Code of Federal Regulation Part 20 Appendix B.
- National Institute of Standards and Technology, ESTAR: Stopping Power and Range Tables for Electrons, July 2017
- Nuclear Regulatory Commission, Varskin+ Version 1.0
- Smith, D., Stabin, M. Exposure Rate Constants and Lead Shielding Values for over 1,100 Radionuclides. Health Physics Journal. March 2012.
- Stanford Environmental Health and Safety. Safety Fact Sheets. <https://ehs.stanford.edu/safety-fact-sheets>